



### Smart Features

- Lightweight and ergonomic design
- Guaranteed durability, supporting more than 1.5 million triggers in 30 continuous days
- The fastest speed among scanners of its class, 150 readings per second
- 3 mil resolution and reading distance from 0 to 90 mm, allows to recognize barcodes with high density, with thinner and smaller bars
- Plug and play device, compatible with Windows, Linux or Android



# BR400

## Barcode Scanner

Number 1 in accuracy and reliability in its category, the BR400 is the right addition to your Point-of-Sale solution. It is designed for easy and comfortable use. The BR400 is built for various environments and can sustain rigorous daily operations. It can correctly recognize the most common 1D barcodes, even if they are printed on reflective material with low resolution or have a damaged label. The BR400 provides agility and efficiency at the POS counter for small businesses



[bematechus.com](http://bematechus.com)



# BR400 SCANNER SPECIFICATION

<b>Type</b>	Portable
<b>Technology</b>	2500 pixel CCD Linear
<b>Light source</b>	LED red 625nm
<b>Reading speed</b>	150 reads per second
<b>Reading Distance</b>	0 ~ 90 mm
<b>Resolution</b>	3 mil
<b>Print contrast</b>	25% @ 100% UPC/EAN
<b>Buzzer</b>	Volume adjustment and time
<b>LED indicators</b>	Blue and Red
<b>Interfaces</b>	USB
<b>Barcodes</b>	Linear 1D codes UPC/EAN/JAN, UPC-A, UPC-E, EAN-8, EAN-13, EAN-128, JAN-8, JAN-13, Code 39, Code 93, Code 128, Code 32, Code 11, Codabar, IATA Code, MSI/Plessey, ISBN/ISSN, Interleaved 2-5, Industrial 2 of 5, Standard 2-5 14, RSS, RSS, RSS Expanded Limited, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, China Postal Code, Telepen.
<b>Certifications</b>	EMC CE and FCC Doc Compliance, VCCI, BSMI
<b>Dimensions (WxDxH)</b>	72 mm x 54 mm x 166 mm
<b>Weight</b>	.22 lbs (without cable)
<b>Cable</b>	1, 5 m ± 5
<b>ELECTRIC</b>	
<b>Input power</b>	+ 5V +/-5%
<b>Operating power (typical)</b>	150mA (max)
<b>Environmental</b>	
<b>Operating temperature</b>	32°-122° F
<b>Storage temperature</b>	-4-140° F
<b>Moisture</b>	5%-95%
<b>Shock/Fall</b>	up to 1.5 m
<b>Light level</b>	6,000 LUX fluorescent lamp max.