



### Smart Features

- LCD display with LED backlight
- Optimal display resolution 800 x 600
- No ventilation hole design
- Light weight, only 1.5lb physically for display without the pole and base.
- VESA 75 x 75 mm wall mount standard
- True flat panel screen

# LV4000U

## LCD Pole Display

Bematech LV4000U is a true flat LCD customer display with compact and ecological design. The power consumption is only 2.5W with LED backlight. It can deliver multi-media messages and transaction information at the same time.



[bematechus.com](http://bematechus.com)



# LV4000U SPECIFICATION

<b>Color</b>	Black
<b>Display size</b>	8"
<b>Display Area</b>	162.0 x 121.5 mm
<b>Optimal Resolution</b>	800 x 600
<b>Brightness</b>	250 cd/m <sup>2</sup> (typ)
<b>Contrast Ratio</b>	500:1 (typ)
<b>Response Time</b>	25 ms (typ)
<b>LCD Viewing Angle</b>	140 degrees (H) 120 degrees (V)
<b>Input signal connector</b>	USB Type B
<b>Input Frequency</b>	Horizontal: 31.5-60.2 kHz
<b>Power consumption</b>	Vertical : 56.3Hz~75Hz
<b>Power supply</b>	500mA/2.5W DC 5V +/- 5%
<b>Temperature</b>	Operating : 0°C~40°C Storage : -10°C~50°C
<b>Humidity</b>	Operating : 20%~80% Storage : 10%~90%
<b>Weight</b>	3.0 lb
<b>Physical Dimension</b>	15.75"H x 7.9"W x 5.9"D
<b>Approvals</b>	CE, FCC
<b>Wall Mount</b>	VESA 75 x 75 mm
<b>Stand Base</b>	7" pole + Base