



### Features

- True-flat, bezel-free, fanless design
- High performance Intel Quad-Core processor
- Durable and sturdy base
- Easy to change or replace hard disk drive
- Optional MSR and VFD/LCD customer display

# SB1015

## True-flat All-in-One Touch POS Terminal

The Bematech SB1015 AIO terminal packs great features and value into a sleek and sturdy design. The unit delivers an economical POS solution while providing excellent performance and reliability. The highly rugged touch monitor includes a solid base with extra wide hinge for maximum stability. The SB1015 also facilitates options for a quick and professional mounting of integrated magnetic stripe reader and VFD/LCD customer display.



# SB1015 SPECIFICATIONS



## ELECTRICAL

Power supply	DC 12V 90W external power adapter
Input to power adapter	100 to 240VAC, 50/60Hz

## MAINBOARD

CPU	Intel Celeron J1900 Quad-Core 2.0GHz
IO chipset	Fintek F71869
Memory	DDR3L 1333 SODIMM slot, up to 8GB
Ethernet LAN	Realtek RTL8111G PCI Express Gigabit LAN
Audio	ALC887 Audio CODEC, HD Audio CODEC
Storage	SATA 2.5in Hard Disk Drive/SSD, mSATA SSD



## DISPLAY

Touch screen	5 wire resistive touch, optional projected capacitive touch
Touch controller	USB interface
LCD panel	15in LED-backlit TFT display, XGA 1024 x 768, 250 nits

## I/O PORTS

USB ports	USB 2.0 x5, USB 3.0 x1
Serial ports	RS232 DB9 x3
Ethernet	Gigabit, RJ45 x1
Video port	VGA DB15 x1
Audio port	Line out x1



## ENVIRONMENTAL

Operating temperature	32°F to 104°F (0°C to 40°C)
Relative humidity	8% to 80%, non-condensing

## MECHANICAL

Dimensions (W x H x D )	14.33in x 12.83in x 9.06in (36.4cm x 32.6cm x 23cm)
Weight	13lbs (5.91Kg)

\*Images shown with available customer display and MSR options