

LR200M

Mobile Thermal Receipt Printer

Features

- Mini size with rubber protection
- Non-slip design
- Power indication light
- Support USB, power adapter or mobile power charging
- Standby mode to save power
- Secure belt strap included



Overview

LR200M portable printer optimizes the mobile checkout process and helps accelerate business at the Point of Sale. The printer is equipped with both Bluetooth and Wi-Fi interface, enabling it to work with POS applications designed for either wireless communications.



3 Year Depot
Warranty



Rugged Durability



Dedicated Customer
Support



LR 200M MOBILE THERMAL RECEIPT PRINTER

PRINTING	
Printing Method	Thermal line printing
Resolution	203 dpi (8 dots/mm)
Paper Width	56 mm
Printing Width	48 mm
Paper Thickness	60 to 80 µm
Paper Roll Diameter	φ40mm max
Character Font	ASCII Font A: 12x24 ASCII Font B: 9x24 ASCII Font C: 9x17 ASCII Font D: 8x16
Printer Density	384 dots/line
Printing Speed	80 mm/s
NV Bitmap Flash	64Kb
Receipt Buffer	8Kb
LIFESPAN	
MCBF	5,000,000 lines
Printer Head Lifetime	50 km
BATTERY	
Type	Rechargeable Li-ion battery
Capacity	1400mAH
Operation time	Continuous
Charging time	3 to 5 hours
Lifespan	>500 recharge cycles
Charging port	USB or power adapter (Standalone desktop charger option available)
ELECTRICAL	
Power adapter input	AC 100-240V, 50/60Hz
Power adapter output	DC 12V, 1A
Power adapter input	AC 100-240V, 50/60Hz
COMMUNICATION	
Interfaces	Bluetooth (BT4.0 EDR & BLE), WiFi, and USB
CONNECTORS	
USB	Standard Mini USB female
Power (for charger)	2.5mm power plug
OPERATIONS	
Paper Sensor	Supported
Printing Commands	ESC/POS
Power Alarm	Low battery indicators
Barcode types	CODE39, EAN-13, EAN-8, CODABAR, CODE93, ITF, QR, PDF417
MECHANICAL	
Weight	260g (0.57 lbs) Including paper roll and battery
Dimension (LxWxH)	112mm x 79mm x 45mm (4.4" x 3.1" x 1.8")
Weight	260g (0.57 lbs) Including paper roll and battery
Dimension (LxWxH)	112mm x 79mm x 45mm (4.4" x 3.1" x 1.8")
ENVIRONMENT	
Operating temperature	-10°C to 50°C
Relative humidity	20% to 85%, non-condensing
Storage temperature	-20°C to 70°C
Relative humidity	5% to 95%, non-condensing

ORDERING INFORMATION

Model	Interface	Color	Availability
		Black	Worldwide

OPTIONAL PERIPHERALS/ACCESSORIES

Part Number	Peripheral



Please visit us bematechus.com, or contacts us at: (516) 248-0400 | sales@bematechus.com